



ROCLAND

Roc Finish

Floor care

Product description

Roc finish is a very hard mono-component water-based emulsion designed to protect floors and to help in their upkeep.

Roc finish is formulated for use on concrete and paving.

Technical specifications

Aspect:	Milky white liquid
Density:	1.1 ± 0.1
Non-flammable	
pH :	8.0 ± 0.1
Application temperature:	5 to 30 °C

Packaging

20 litres drum.

The product can be stored one year in its original container, kept in a closed place and protect from frost.

Method statement

- On surfaces consisting of **Roc cure**, strip this using **Roc decap**.
- On surfaces free of any treatment (curing products, wax or similar) , neutralised using **Roc neutre**, apply one coat of **Roc finish** using an application sleeve or airless spray; Wait for this coat to dry completely before applying a second layer for a satin finish.

Can be walk on after 24 hours at 20 °C
Fully useable after 36 hours at 20 °C

Roc neutre with daily upkeep, and **Roc polish** with weekly or monthly depending on conditions are particularly adapted to make the treatment with **Roc finish** more durable.

Coverage

Approximately 1 litre for 10 m² (minimum two layers).

Health and safety

Non dangerous good.

Refer to our safety data sheet.

Note:

Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it and that the actual conditions of use are suitable.

Z.A. Les Monts du Matin
Rue des Lauriers
F-26730 La Baume d'Hostun
France
Tél. : + 33 (0)4 75 48 37 50
Fax : + 33 (0)4 75 48 30 03
www.rocland.eu

P L A C E O