

# Maintenance and cleaning

You are to be the owner of a surface based on concrete floor hardeners, colored or not.

Curing membrane may change the surface look. Those products may change the gloss and aspect of the surface.

In order to preserve this floor, it's greatly recommended to respect some basic recommendations.

# Protection and maintenance of the surface

After finishing operations, the surface stays microporous. In order to limit the penetration of liquids and oils, facilitate the cleaning of the surface, it is greatly recommended to protect the surface with products and techniques adapted.

## Cleaning of the surface

Concrete cure done with Roc cure:

- 1 Roc **Decap** (stripper-grease remover)
- 2 Cleaning with Roc Neutre (neutralising-cleaning agent)
- 3 Roc *Seal* (waterproof and oil proof sealer)

#### Concrete cure done with **Ecocure 17**:

- 1 Roc Neutre (neutralising-cleaning agent)
- 2 Roc Finish (impregnation and pore filler)

#### **Daily cleaning**

- Roc **Polish** (waxing floor upkeep)
- Roc **Neutre** (neutralising-cleaning agent)

#### **Specific cleaning**

- Roc *Détachant* (cleaning product)
- Roc *Neutre* (neutralising-cleaning agent)

## Saw cut joints

We recommend to fill the saw cut joints with the following products:

# Temporary joint sealing

• Roc *Plast 55* 

#### **Definitive joint sealing**

• Roc *Joint ES 10* 

or

• Roc Joint PU 920/925

All our technical and safety data sheet are on our web



#### Note

Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it and that the actual conditions of use are suitable.

