



ROCLAND

Roc Polish

Floor care

Product description

Roc polish is a polymer, wax and surface-active agent based emulsion which gives deep cleaning whilst depositing a high-gloss protective film.

Roc polish helps in the maintenance of industrial floors.

Roc polish is recommended for all concrete floors and specially for floors treated with Roc finish or Roc seal.

Technical specifications

Aspect:	white milky liquid
Density:	1.0 ± 0.1
Non-flammable	
pH:	7 - 8
Application temperature:	5 to 30 °C

Packaging

20 litres drum.

The product can be stored one year in its original container, kept in a closed place and protect from frost.

Note :

Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it and that the actual conditions of use are suitable.

Method statement

With weekly or monthly upkeep depending on conditions, after cleaning the surface with **Roc neutre**, apply **Roc polish** diluted with water (for example 1 part of **Roc polish** for 9 parts of water) using a buffer or applicator sleeve. The gloss and degree of protection are directly linked to the concentration of product.

However, to bring out the polish, on dry surface, pass over a machine fitted with a cream or white disc at high speed.

Coverage

Between 1 litre per 20 m² for neat application and 1 litre per 200 m² in a 10 % concentration.

Application depends on the gloss finish and protection desired.

Health and safety

Non dangerous good.

Refer to our safety data sheet.

Z.A. Les Monts du Matin
Rue des Lauriers
F-26730 La Baume d'Hostun
France
Tél. : + 33 (0)4 75 48 37 50
Fax : + 33 (0)4 75 48 30 03
www.rocland.eu

PLACEO